

# TD SHADES

Natural oil based staining product for interior veneer & wood surfaces.



COATS

Natural Wood Finishing Oils



CERT. EN-71.3

CERT. IBR

Technical Data Sheet 04/05/2018.

## DESCRIPTION

TD Shades is a unique mixture of natural oils, resins & pigments that forms a perfect stain coat on a veneer/ wood surface; that is to be consequently treated with natural oils for surface finishing. As it is formulated on structurally thin oils, it penetrates deeply into the veneer/ wood and provides uniform color toning to the surface.

## PHYSICAL & CHEMICAL PROPERTIES

Appearance	:	Liquid
Density	:	850 grams/ litre
Solid Content	:	46-48%
Colour	:	Sapeli/ Smoked sapeli/ Light walnut/ Medium walnut/ Dark walnut/ Teak/ Wenghe/ Light grey/ Dark grey/ White/ Black/ Santos
Odour	:	Typical
Yield	:	200-225 Square Feet on single coat basis depending on veneer/ wood specie
Dilution	:	Not Required
Cleaning of Tools	:	White Spirit
Application	:	Spray/ Brush/ Roller/ Rag
Number of Coats	:	1 coat

## HOW TO USE

- Provide a clean degreased veneer/ wood surface sanded 150 grit.
- Spray evenly and allow for 3-4 hours of drying time.
- Excess atmospheric humidity or low temperatures can prolong drying time.
- Sand lightly with 180 grit sand paper.
- Spray TD base as a sealer coat; allow for 3-4 hours of drying time.
- Fill nail marks with standard wood putty.
- Use TD Base for light recoating of the veneer/ wood surface after filling nail marks.
- Follow up with subsequent top coat treatments.

## GENERAL INSTRUCTIONS

- Shake/stir well before use.
- Keep out of reach of children.
- Repeated exposure may cause skin dryness or cracking.
- Cloth, Rags, Sanding papers, Buffing Pads used along with these products should be soaked in water and then discarded. Unattended waste can cause self-ignition.

# TD SHADES

Natural oil based staining product for interior veneer & wood surfaces.



COATS

Natural Wood Finishing Oils

## PACKAGE

The product comes in 1 litre/ 10 litre/ 20 litre Cans.

## STORAGE

Keep in cool, well ventilated place. When not in use, keep the container close. Provide safe distance from flames, sparks and other sources of ignition.

## DECLARATION

Our technical data sheets formulated based on our laboratory tests. Application instructions and technical advice is suggestive. Applicator skills, base veneer/ wood specie, working environments, equipment used, dilutions form integral parts of the final result achieved on the coated surface. The cumulative effect of various permutations and combinations of these factors are difficult to predict. Thus we highly recommend that the user/ specifier/ final consumer must test the products for suitability and results in their specific environment. We can always assure the consistency of the physical and chemical characteristics of the material supplied.